

Date	Req Delivery	Agent
End User		Actuator Competition
Project		Valve Competition

VALVE DATA				CONTROL COMPONENT DATA					
Quantity	Size	Class		On / Off Service	<input type="checkbox"/> Starter	<input type="checkbox"/> Transformer	<input type="checkbox"/> Pushbuttons		
Type	<input type="checkbox"/> Ball	<input type="checkbox"/> Plug	<input type="checkbox"/> BFV	Modulating/ Throttling Service <small>(Requires reversing starter as minimum)</small>	<input type="checkbox"/> Lights	<input type="checkbox"/> Selector Switch			
	<input type="checkbox"/> Sluice / Slide Gate				<input type="checkbox"/> Servo (4-20ma)	<input type="checkbox"/> Retrans (4-20ma)			
Keystone Figure #			<input type="checkbox"/> Fail in last position card						
Stem	Diameter	Height			<input type="checkbox"/> Potentiometer				
	Key Size			<input type="checkbox"/> Solid-state Starter (on/off or mod)					
Torque	Seating	lb. in.		<input type="checkbox"/> Overload Relays	<input type="checkbox"/> Phase Correction				
	Unseating	lb. in.		Interposing Relays <input type="checkbox"/> 3 <input type="checkbox"/> 2 <input type="checkbox"/> 1 (monitor)					
	Dynamic	lb. in. at °		<input type="checkbox"/> Phase Discriminator	<input type="checkbox"/> Speed Control				
	Safety Factor Included?	<input type="checkbox"/> No <input type="checkbox"/> Yes		<input type="checkbox"/> Teflon Wire (high or low temp. service)					
ACTUATOR DATA									
Service	<input type="checkbox"/> On/Off		<input type="checkbox"/> Modulating		Additional Electrical Components	<input type="checkbox"/> Sleeve-type Wire Markers			
	<input type="checkbox"/> Throttling (position feedback only)					<input type="checkbox"/> Heavy-gauge Control Wire (16-gauge is std.)			
Operating Speed	sec. (1/4 turn)			Additional Mechanical Components		<input type="checkbox"/> Motor Heater	<input type="checkbox"/> Space Heater Thermos		
	in./min (multi-turn)					<input type="checkbox"/> Fused Disconnect	<input type="checkbox"/> Circuit Breaker		
Ambient Temp. ° F or ° C						<input type="checkbox"/> Un-fused Disconnect	<input type="checkbox"/> Class H Motor Insulation		
KCI to Adapt?	<input type="checkbox"/> Yes		<input type="checkbox"/> No			Additional Mechanical Components	<input type="checkbox"/> Remote Control Box		
	<input type="checkbox"/> Yes		<input type="checkbox"/> No				<input type="checkbox"/> Stem Covers	<input type="checkbox"/> Plastic <input type="checkbox"/> Steel	
Actuator Orientation	<input type="checkbox"/> Horizontal		<input type="checkbox"/> Gearhead mounted separate from electric actuator (77W, 77E)			<input type="checkbox"/> Special Graduation on Local Dial Indicator			
	<input type="checkbox"/> Vertical					<input type="checkbox"/> Floorstand <input type="checkbox"/> Nylon Stem Nut			
Req. Rimpull	lb. ft					Special Services	<input type="checkbox"/> Special Paint		
Enclosure	<input type="checkbox"/> NEMA 4, 4X		<input type="checkbox"/> CSA		<input type="checkbox"/> Special Hardware				
	<input type="checkbox"/> NEMA 6		<input type="checkbox"/> Explosion Proof		<input type="checkbox"/> Packaging				
	<input type="checkbox"/> Other				<input type="checkbox"/> Field Service <input type="checkbox"/> Source Inspection				
Motor Power Supply	3 Phase	<input type="checkbox"/> 230	<input type="checkbox"/> 575	<input type="checkbox"/> 208	Special Services	<input type="checkbox"/> Testing			
		<input type="checkbox"/> 460	<input type="checkbox"/> 380 50 Hz						
Control Power Supply	1 Phase	<input type="checkbox"/> 120	<input type="checkbox"/> 220	<input type="checkbox"/> 208					
	<input type="checkbox"/> 120 VAC		<input type="checkbox"/> 220 VAC						
Limit Switches	<input type="checkbox"/> Source at site			Comments					
	<input type="checkbox"/> (6) SPDT (std.)								
Auxiliary Gear Head (77W)	Service	<input type="checkbox"/> AWWA		<input type="checkbox"/> Industrial					
		<input type="checkbox"/> Hi-Temp		<input type="checkbox"/> Submersible					
	Rotation	<input type="checkbox"/> 90°		<input type="checkbox"/> 180°					
<input type="checkbox"/> 270°		<input type="checkbox"/> 360°							





Fax

To: Centro, Inc.	From:
Fax: 901-357-1379	Pages:
Phone: 800-344-3286	Date:
Re:	CC:

Please fill out this specification form and fax to one of the three locations:

Memphis: 901-357-1379

Little Rock: 501-835-2277

Nashville: 615-255-2212